

HDS 9/20-4 CLASSIC

Reliable, easy to operate hot water high-pressure cleaner, with excellent price/performance ratio and equipped with a high-quality crankshaft pump as well as a robust tubular steel frame.



2

Order no.

1.030-910.0

- Robust crankshaft pump
- Outstanding price-performance ratio
- Robust tubular steel frame

Technical data

Tech	nical data		
EAN	code		4054278956138
Supp	ly voltage	Ph / V / Hz	3 / 400 / 50
Flow	Rate	l/h	300 - 900
Oper	ating pressure	bar / MPa	30 - 200 / 3 - 20
Tem	perature (supply 12°C)	°C	max. 80
Powe	er rating	kW	7
Cons	umption fuel oil	kg/h	5.8
	ing oil consumption, Afficiency	kg/h	4.7
Powe	er cable	m	5
Fuel	tank	1	30
Weig	ht (with accessories)	kg	124
Weig	ht incl. packaging	kg	134
Dime	ensions (L × W × H)	mm	1075 × 722 × 892

Equipment		
Trigger gun		Standard
High-pressure hose	m	10 / ID 8, 315 bar
Spray lance	mm	1050
Power nozzle		
ANTI!Twist		
Pressure switch control		
Pole reversing plug (three-phase)		
Included in delivery.		

HDS 9/20-4 Classic, 1.030-910.0, 2024-10-24

Users must receive training on this device.





Robust and long-lasting

- A robust tubular steel frame reliably protects the machine against damage.
- Good accessibility for easy service and maintenance.



Reliability

- Robust crankshaft pump with proven Kärcher quality.
- Proven safety technology such as thermo and safety valve and water filter.



Efficient burner engineering

- High degree of efficiency with low emissions and long life.
- Long work applications thanks to 30-I fuel tank.
- \bullet In ecolefficiency mode, the machine operates in the most economical temperature range (60 $^\circ \rm C)$ with full water flow.

EQUIPMENT FOR HDS 9/20-4 CLASSIC 1.030-910.0



				—
		Order no.	Description	
TRIGGER GUNS				_
Pistol TR 155°C with package	1	4.119-002.0	High-quality Classic spray gun with robust valve. Also suitable for Kärcher hot water high-pressure cleaners.	
EASY!Force conversion kit 1 - from high-pressure hose	2	4.111-050.0	For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle.	
EASY!Force conversion kit 2 - from machine	3	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	
EASY!Force conversion kit 3 - high-pressure gun	4	4.111-052.0	Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.	
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 25°				
Power nozzle 25°, 047	5	2.113-009.0	Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	
HP nozzle spray angle 0°				
Power nozzle 0°, 050	6	2.113-034.0	High-pressure nozzle with powerful jet for extremely stubborn dirt.	
Power nozzle spray angle 15°				
Power nozzle 15°, 055	7	2.113-047.0	Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	
Power nozzle spray angle 40°				
Power Nozzle 40°, 050	8	2.113-054.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	
SPRAY LANCES				
Rotating spray lances				
LED nozzle light	9	2.680-002.0	Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.	
Spray lance, 250 mm, rotatable	10	4.112-027.0	Spray lance, 250 mm, rotatable, ergonomic	
Spray lance, 400 mm, rotatable	11	4.112-024.0	Spray lance, 400 mm, rotatable, ergonomic	
Spray lance, 600 mm, rotatable	12	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 840 mm, rotatable	13	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1550 mm, rotatable	14	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
			1	

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR HDS 9/20-4 CLASSIC 1.030-910.0



		Order no.	Description	
SPRAY LANCES		0.001		
Rotating spray lances				
Spray lance, 2050 mm, rotatable	15	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance extender, 1000 mm	16	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.	
Double lance				_
Double lance, 960 mm	17	2.112-016.0	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance				
WC and gutter lance	18	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance				
Flexible lance, 1050 mm	19	4.112-035.0	1050 mm flexible lance with variable bend from 20° to 140° , ideal for cleaning difficult to reach areas, e.g. gutters.	
High pressure articulated joint	20	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Gutter cleaner		•		
Gutter cleaning lance	21	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the specia nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance				
Underbody lance	22	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle				
Additional handle for EASY!Lock spray lances	23	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.	
WEED CONTROL				
WR 10	24	2.114-016.0	In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter.	
ECO!BOOSTER				
eco!Booster TR 050	25	2.113-088.0	ecolBooster with 50% higher area performance than the Kärcher power nozzle; ideal for delicate surfaces. For cold and hot water high-pressure cleaners (nozzle size 050).	
QUICK CONNECT				
Quick-fitting pipe union coupler trapezo	26	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 \times 1.5 internal thread.	
Quick-fitting pipe union plug nipple tra	27	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 \times 1.5 external thread.	
DRUM AND TANK CLEANING				
Add-on kit mud sucker	28	2.641-798.0		
■ Included in delivery. □ Available accesso	ories.			

ded in delivery. ☐ Available acce

EQUIPMENT FOR HDS 9/20-4 CLASSIC 1.030-910.0

















31





		Order no.	Description	
ADD-ON KITS		Order no.	Description	
Add-on kit float HDS Classic	29	2.394-003.0		Iг
Add-on kit hour counter	30	2.853-192.0		E
OTHER HP ACCESSORIES				_
Jet gun	31	2.869-067.0	Short set-up time, easy transport, instant switch off - the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	
FLUE PIPE				Ļ
Flue gas adapter	32	4.656-149.0	Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for connection to a stack system).	
ROTARY NOZZLES (DIRT BLASTERS)				
Dirt blaster, large				
Dirt blaster Vibrasoft, 050	33	4.114-066.0	Vibrasoft rotary nozzle with rotating point jet for ten times greater cleaning performance. Durable dirt blaster thanks to ceramic nozzle. Reduces vibrations by up to 30% for maximum ergonomics.	
Dirt blaster, large, 050	34	4.114-027.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	зĽ
MULTIPLE-JET NOZZLES				
Angle vario nozzle 0°-90°				
Angled Vario nozzle, 055	35	4.113-008.0	Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.	f
STEAM NOZZLE / NOZZLE PROTECTOR / ROL	LOVER N	OZZLE		
Steam nozzle				
Steam jet nozzle 50°	36	4.116-000.0	Steam jet nozzle with 50°fan jet. For cleaning and thawing in steam stage. For thawing sand and gravel, de-icing formwork material or de-waxing vehicles.	
NOZZLE UNION / SPACER				
Nozzle union				
Nozzle screws	37	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles	
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 10 m, ID 10, 220 bar, 2 × EASY!Lock	38	6.110-041.0		
High-pressure hose, 10 m, ID 8, 315 bar, 2 × EASY!Lock	39	6.110-031.0	10 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 15 m, ID 8, 315 bar, 2 × EASY!Lock	40	6.110-030.0	15 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 20 m, ID 8, 315 bar, 2 × EASY!Lock	41	6.110-032.0	20 m high-pressure hose (M 22 × 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}C/315$ bar.	
High-pressure hose, 30 m, ID 8, 315 bar, 2 × EASY!Lock	42	6.110-014.0	With rotary coupling, 2 × M 22 × 1.5	

EQUIPMENT FOR HDS 9/20-4 CLASSIC 1.030-910.0

55

0

56-58





Order no. Description **HIGH-PRESSURE HOSES** Standard with unions on both sides High-pressure hose, 15 m, ID 10, 220 bar, 43 6.110-042.0 15 m high-pressure hose M 22 \times 1.5) with kink protection and threaded couplings at both ends. 2 × EASY!Lock Further data: DN 10/155°C/220 bar. High-pressure hose, 20 m, ID 10, 220 bar 44 6.110-043.0 with union on both sides, M 22 × 1.5 with anti-kink protection. NW 10/155°C/220 bar 2 × EASY!Lock High-pressure hose, 25 m, ID 10, 220 bar, 6.110-044.0 45 2 × EASY!Lock High-pressure hose, 40 m, ID 10, 220 bar, 6.110-045.0 46 2 × EASY!Lock High-pressure hose, 15 m, ID 12, 210 bar, 47 6.110-059.0 High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 2 × EASYILock 22 × 1.5 with anti-kink protection. High-pressure hose, 40 m, ID 12, 210 bar, 48 6.110-060.0 2 × EASY!Lock Longlife 400 with unions on both sides High-pressure hose Longlife, 1,5 m, ID 8, 400 49 6.110-024.0 1.5 m high-pressure hose (DN 8, M 22 \times 1.5) with kink protection and connectors at both ends. For bar, 2 × EASY!Lock connecting to hose reels with appropriate connector (M 22×1.5). High-pressure hose Longlife, 30 m, ID 8, 400 50 6.110-023.0 With rotary coupling, 2 × M 22 × 1.5 bar, 2 × EASY!Lock High-pressure hose Longlife, 20 m, ID 8, 400 51 6 1 1 0 - 0 2 7 0 with rotary coupling, 2 × M 22 × 1.5 bar, 2 × EASY!Lock 52 6 1 10 - 0 29 0 High-pressure hose Longlife, 15 m, ID 8, 400 With rotary coupling, 2 × M 22 × 1.5 bar. 2 × FASY!Lock Food industry version with unions on both sides High-pressure hose food grade, 10 m, ID 8 53 6 1 1 0 - 0 5 1 0 10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector 250 bar, 2 × EASY!Lock Non-discolouring outer layer for use in the food industry. M 22 × 1.5 with anti-kink sleeve High-pressure hose food grade, 20 m, ID 8, 54 6.110-052.0 20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 × 1.5, with kink protection. NW 8/155°C/250 bar. 250 bar, 2 × EASY!Lock Longlife food industry version with unions on both sides High-pressure hose food grade Longlife, 10 m. 55 6.110-053.0 With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), ID 8, 400 bar, 2 × EASY!Lock 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends PIPE CLEANING Pipe cleaning hose, ID 6 Hose assembly TR pipe cleaning DN6 max.2 56 6.110-046.0 The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).

□ Available accessories.

54

EQUIPMENT FOR HDS 9/20-4 CLASSIC 1.030-910.0



70

69

	_			
		Order no.	Description	
PIPE CLEANING				
Pipe cleaning hose, ID 6				
Pipe cleaning hose, DN 6, 20 m, 220 bar	57	6.110-008.0	20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	58	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle				-
Dirt blaster pipe cleaning D21/060	59	4.765-002.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted	
Dirt blaster pipe cleaning D30/060	60	4.765-005.0	jets ensure the necessary forward movement, as well as convenient handling.	
Nozzle pipe cleaning size 80	61	5.763-087.0	Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	62	5.763-015.0	16 mm pipe cleaning nozzle with internal thread. Various jet directions for	
	63	5.763-016.0	environmentally-friendly cleaning of blocked drains and pipes.	
	64	5.763-017.0	30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
Add-on kit dirt trap	65	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	
Hard surface cleaner FR 30 ME	-			
FR 30 ME surface cleaner	66	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Hard Surface Cleaner FR 50				
FR 50 surface cleaner	67	2.111-023.0	Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	
Machine-specific nozzle kit for FR				
Nozzle kit for FR, 850 l/h - 1100 l/h	68	2.640-442.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).	
Machine-specific nozzle kits for FRV				-
Nozzle kit for FRV, 050	69	2.642-433.0	Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	
Hard surface cleaner FRV 30 Me			·	
FRV 30 Me Surface Cleaner	70	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	

EQUIPMENT FOR HDS 9/20-4 CLASSIC 1.030-910.0

71 71	7	3		
78	8			- °
		Order no.	Description	
FLOOR AND HARD SURFACE CLEANER				
Hard surface cleaner FRV 30 Me				
Extension hose FRV 30 Me and FRV 50 Me	71	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	
FOAM SYSTEMS				
Cup foam lance				
Cup foam lance Advanced 3, 900 l/h - 2500 l/h	72	4.112-065.0		
Cup foam lance DUO Advanced 3, 900 I/h - 2500 I/h	73	4.112-069.0		
Cup foam lance Basic 3, 900 l/h - 2500 l/h	74	4.112-055.0	For high-pressure cleaners with a flow rate of 900-2500 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.	
1-litre cleaning agent container for cup foam lance basic	75	5.071-414.0		
1-litre cleaning agent container for cup foam lance advanced	76	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
Inno Foam Set				
Inno foam kit with detergent injector	77	2.112-000.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For	
Inno foam kit	78	2.112-008.0	use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	
Easy Foam Set				
Easy Foam Set with RM injector	79	2.112-010.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for	
Easy foam set	80	2.112-011.0	connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	
Nozzle kits for Inno/Easy Foam Set				
Nozzle kit 090 Inno/Easy kit 700 - 1000 I/h	81	2.111-019.0	Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 I/h. For optimal foam system performance.	
MIXERS AND INJECTORS				
HP detergent injector				
Detergent injector for high and low pressure (without nozzles)	82	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Detergent injector for high pressure	83	4.637-033.0	Cleaning agent dosage at high pressure 3 - 5 %	
Machine-specific nozzle kit with order no. 3.63	37-170	5		_
Nozzle insert trapezoidal thread HDS-GER	84	4.769-011.0	For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP power nozzle + union	

□ Available accessories.

EQUIPMENT FOR HDS 9/20-4 CLASSIC 1.030-910.0

95

94

93



97

98

96

		1		—
		Order no.	Description	
MIXERS AND INJECTORS				
Nozzle insert with order no. 3.637-001				
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	85	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to 1100 l/h	86	4.769-001.0	For low pressure with machines up to 1.100 l/h	
COUPLING PARTS				
Rotary coupling				
Rotary coupling	87	4.111-021.0	Kårcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector Easy!Lock. With grip protection.	
Connector				
Nozzle connector/screw connector	88	4.111-022.0	Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 × 1.5 and 1x M 18 × 1.5.	
Y distributor	89	4.111-024.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	
Short spray unit	90	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.	C 🗆
Adapter EASY!Lock				-
Adapter 1 M22AG-TR22AG	91	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	92	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	93	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter M22 – Swivel	94	4.111-032.0	M22 × 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	
Adapter 5 TR22IG-M22AG	95	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	96	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	97	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	98	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	

EQUIPMENT FOR HDS 9/20-4 CLASSIC 1.030-910.0

99 100	1	01		
106	1	08		ン
		Order no.	Description	
COUPLING PARTS				
Adapter EASY!Lock				
Coupler -2xM22x1,5	99	4.111-037.0	Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \ M \ 22 \ \times \ 1.5 \ m.$	
ADAPTER for replacement TR22IG-M22AG Er	100	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	
HOSE REELS				
Hose reel add-on kit				
Add-on kit hose reel HDS Classic	101	2.639-353.0		
Anbausatz Schlauchtrommel automatik				
Attachment kit automatic hose reel holder HDS M/S	102	2.110-020.0	Holder includes connection material for installing an automatic hose reel to machines in the HDS Middle and Super classes.	
FACADE AND SOLAR PANEL CLEANING				
Brushes				
Drive for roller brush 500	103	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.	
Splash guard for roller brush 500	104	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.	
Roller brush 500 soft	105	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.	
Roller brush 500 medium	106	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.	
Roller brush 500 hard	107	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.	
Brush hard	108	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	
Brush medium	109	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.	
Brush soft	110	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	
iSolar 800 Advanced	111	6.368-094.0	iSolar 800 water-driven brush head, 800 mm wide, for water flow rates of 700-1,000 l/h. With two contra-rotating disc brushes and flexible angle joint. For photovoltaic systems.	
iSolar 400 Advanced	112	6.368-092.0	iSolar 400 brush for water flow rate of 700-1,000 l/h. The water-driven disc brush with a width of 400 mm cleans small to medium-sized photovoltaic systems. Also perfect for use on elevated systems.	

EQUIPMENT FOR HDS 9/20-4 CLASSIC 1.030-910.0



		Outerra	Provide the second s			
FACADE AND SOLAR PANEL CLEANING		Order no.	Description			
Telescopic				-		
TL low pressure adapter	113	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.			
Telescopic lance TL 7 F	114	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.			
Telescopic lance TL 7 H	115	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix Telescopic thanks to quick-release fastenings. Up to 7 m reach.			
Telescopic lance TL 10 H	116	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.			
Telescopic lance TL 10 C	117	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.			
Telescopic lance TL 14 C	118	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.			
TL high pressure adapter	119	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.			
Wasserenthärtung				-		
WS 50	120	6.368-463.0	The mobile WS 50 water softening unit prevents lime residue on clean surfaces. A special ion-exchange resin removes the dissolved limescale from the water.			
WS 100	121	6.368-464.0	The mobile WS 100 water softening unit prevents lime residue on clean surfaces. A special ion-exchange resin removes the dissolved limescale from the water.			
WS Regenerator	122	6.368-465.0	With the WS Regenerator regeneration system, the softening cartridges of the water softening units WS 50 and WS 100 can be backflushed and regenerated at the push of a button.	s 🗆		
Hoses				_		
Hose solar	123	6.392-978.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.			
	124	6.392-977.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.			
	125	6.392-976.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.			
WET BLASTING ATTACHMENT						
Wet blasting attachment (without nozzle)						
Wet blasting attachment with flow control (without nozzles)	126	4.115-000.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.			

EQUIPMENT FOR HDS 9/20-4 CLASSIC 1.030-910.0

136-137

138



140

139

		Order no.	Description	
WET BLASTING ATTACHMENT				
Wet blasting attachment (without nozzle)				
Wet blasting attachment without flow control (nozzles not included)	127	4.115-006.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	
Nozzle pack for wet blasting attachment				
Nozzle pack TR wet jet set 0055	128	2.112-024.0	Consisting of wet jet nozzle and nozzle insert – only for use in combination with wet jet unit 4.115-000.0 4.115-006.0.	
Boron carbide nozzle				
Boron carbide nozzle, for machines as of 1000 l/h	129	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	
DRUM AND TANK CLEANING				
Barrel and tank cleaning				
Barrel cleaner BC 14/12	130	2.112-020.0	The barrel cleaner BC 14/12 is a spray unit for the internal cleaning of containers and drums – in particular oak barrels with a capacity between 225 and 600 liters.	
Rotary cleaner head M63E	131	6.751-061.0		
Nozzle kit for HKF 50 spray head (3.631-009.0	/ 3.63	31-039.0)		
Nozzle 045 for dual nozzle operation HKF 50 $$	132	6.415-446.0	Nozzle for dual-nozzle operation	
Nozzle 090 for single nozzle operation HKF 50	133	6.415-447.0	Nozzle for single-nozzle operation	
Double handle for exact control of the spray head	134	2.863-036.0	Double handle. Precise control of the spray head	
Screw plug for using a spray head with one nozzle	135	5.411-061.0	Screw plug for using a spray head with one nozzle	
WATER CONNECTION				
Geka coupling				
With hose nozzle, R 3/4"	136	6.388-455.0	with hose liner	
With hose nozzle, R 1"	137	6.388-465.0	with hose barb	
Hose coupling	138	6.388-458.0	with female thread	
Suction filter				
Water filter	139	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve	n 🗆
Suction filter with check valve	140	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	

□ Available accessories.

135

EQUIPMENT FOR HDS 9/20-4 CLASSIC 1.030-910.0



		Order no.	Description	
WATER CONNECTION				
Fine-mesh water filter				
Add-on kit water filter universal	141	2.637-020.0		
Fine-mesh water filter with adapter	142	4.730-102.0	Fine-mesh water filter, 125μ m, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter 1".	·, 🗆
Fine-mesh water filter, 100 µm, R 1"	143	2.638-270.0	Fine-mesh water filter, 100 μ m, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 I/h. Connector 1".	s 🗆
Water supply hose				
Water supply hose	144	4.440-207.0	NW 19 R1" / R 3/4", up to 85 °C, for pick-up	
	145	4.440-270.0	NW 19 R1" / R1", up to 85 °C	
WASHING BRUSHES				
Push-on washing brush				
Push-on wash brush, M 18 × 1.5	146	4.113-001.0	Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 \times 1.6.	
Rotating washing brush				
Rotating wash brush for < 800 l/h machines, nylon bristles	147	4.113-004.0	The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60° C. (M 18 × 1.5, replaceable brush insert).	
Rotating wash brush for < 800 l/h machines, natural bristles	148	4.113-003.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60° C, M 18 × 1.5 (replaceable brush insert).	