

HD 13/18-4 S CLASSIC

The robust HD 13/18-4 S Classic cold water high-pressure cleaner is made for tackling tough jobs day in day out. Super Class in every way: extreme power for reliable cleaning results.



Made in Germany



Order no. **1.367-403.0**

- Robust crankshaft pump with ceramic pistons
- Tubular steel frame
- Outstanding flushing action

Technical data

| | | |
|---------------------------|-------------|--------------------|
| EAN code | | 4054278904184 |
| Supply voltage | Ph / V / Hz | 3 / 376 - 424 / 50 |
| Flow rate | l/h | 700 - 1300 |
| Inlet temperature | °C | 60 |
| Working pressure | bar | 50 - 180 |
| Max. pressure | bar / MPa | 240 / 2.4 |
| Connected load | kW | 8.8 |
| Power cable | m | 5 |
| Nozzle size | | 075 |
| Water inlet | | 1" |
| Colour | | anthracite |
| Weight (with accessories) | kg | 68 |
| Weight incl. packaging | kg | 75.9 |
| Dimensions (L × W × H) | mm | 720 × 637 × 1060 |

Equipment

| | | |
|--|----|--------------------|
| High-pressure hose | m | 10 / ID 8, 315 bar |
| Spray lance | mm | 840 |
| Power nozzle | | ■ |
| Crankshaft pump with ceramic pistons | | ■ |
| 4-pole, three-phase motor with air and water cooling | | ■ |
| Pressure switch-off | | ■ |
| Integrated water fine filter | | ■ |
| Oil level indicator | | ■ |
| Brass water inlet | | ■ |

■ included in the scope of supply.

Users must receive training on this device.




Powerful and robust crankshaft pump with brass cylinder head and pistons with ceramic sleeves

- High performance and high efficiency.
- Long service life and low maintenance costs.
- With suction feature and up to 60 °C water temperature.



Robust steel frame with large wheels for maximum portability

- Protects the machine even in adverse conditions.
- Simple and convenient to transport.
- Integrated storage space for accessories.



Classic accessories with EASY!Lock connections

- Quick set-up and pack-up plus easy accessory replacement.
- Robust and durable accessories.
- Easy and intuitive to operate.

ACCESSORIES FOR HD 13/18-4 S CLASSIC

1.367-403.0



| | | Order no. | Description | |
|---|----|-------------|--|---|
| TRIGGER GUNS | | | | |
| Spray guns | | | | |
| Pistol TR 155°C with package | 1 | 4.119-002.0 | High-quality Classic spray gun with robust valve. Also suitable for Kärcher hot water high-pressure cleaners. | ■ |
| EASY!Force conversion kit 1 - from high-pressure hose | 2 | 4.111-050.0 | For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle. | □ |
| EASY!Force conversion kit 2 - from machine | 3 | 4.111-051.0 | Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters. | □ |
| EASY!Force conversion kit 3 - high-pressure gun | 4 | 4.111-052.0 | Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner. | □ |
| KÄRCHER POWER NOZZLE | | | | |
| Power nozzle spray angle 15° | | | | |
| Power nozzle 15°, 075 | 5 | 2.113-050.0 | Fan jet nozzle with 15° spray angle suitable for stubborn dirt. | ■ |
| Power nozzle 15°, 080 | 6 | 2.113-051.0 | | □ |
| HP nozzle spray angle 0° | | | | |
| Power nozzle 0°, 080 | 7 | 2.113-038.0 | High-pressure nozzle with powerful jet for extremely stubborn dirt. | □ |
| Power nozzle spray angle 40° | | | | |
| Power nozzle 40°, 080 | 8 | 2.113-057.0 | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces. | □ |
| SPRAY LANCES | | | | |
| Rotating spray lances | | | | |
| LED nozzle light | 9 | 2.680-002.0 | Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours. | □ |
| Spray lance, 250 mm, rotatable | 10 | 4.112-027.0 | Spray lance, 250 mm, rotatable, ergonomic | □ |
| Spray lance, 400 mm, rotatable | 11 | 4.112-024.0 | Spray lance, 400 mm, rotatable, ergonomic | □ |
| Spray lance, 600 mm, rotatable | 12 | 4.112-007.0 | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Spray lance, 840 mm, rotatable | 13 | 4.112-006.0 | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Spray lance, 1550 mm, rotatable | 14 | 4.112-018.0 | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR HD 13/18-4 S CLASSIC

1.367-403.0



| | | Order no. | Description | |
|--|----|-------------|---|--------------------------|
| SPRAY LANCES | | | | |
| Rotating spray lance | | | | |
| Spray lance, 2050 mm, rotatable | 15 | 4.112-021.0 | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | <input type="checkbox"/> |
| Spray lance extender, 1000 mm | 16 | 4.112-048.0 | Spray lance extension with EASY!Lock connection. Length 1000 mm. | <input type="checkbox"/> |
| Double lance | | | | |
| Double lance, 960 mm | 17 | 2.112-016.0 | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning). | <input type="checkbox"/> |
| Angular spray lance | | | | |
| Spray lance for toilets and rain gutters | 18 | 4.112-029.0 | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets. | <input type="checkbox"/> |
| Flexible spray lance | | | | |
| Flexible lance, 1050 mm | 19 | 4.112-035.0 | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters. | <input type="checkbox"/> |
| High pressure articulated joint | 20 | 4.112-057.0 | For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer. | <input type="checkbox"/> |
| Gutter cleaner | | | | |
| Gutter cleaning lance | 21 | 2.112-015.0 | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. | <input type="checkbox"/> |
| Undercarriage spray lance | | | | |
| Underbody lance | 22 | 4.112-032.0 | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle. | <input type="checkbox"/> |
| Additional handle | | | | |
| Additional handle for EASY!Lock spray lances | 23 | 4.321-380.0 | Comfortable in every situation - the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360°-rotatable spray lance, the additional handle can simply be fully rotated whilst working for greater flexibility. | <input type="checkbox"/> |
| MULTIPLE-JET NOZZLES | | | | |
| Angled vario nozzle 0-90° | | | | |
| Angled Vario nozzle, 080 | 24 | 4.113-006.0 | Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces. | <input type="checkbox"/> |
| ECO!BOOSTER | | | | |
| eco!Booster TR 080 | 25 | 2.113-089.0 | eco!Booster with 50% higher area performance than the Kärcher power nozzle; ideal for delicate surfaces. For cold and hot water high-pressure cleaners (nozzle size 080). | <input type="checkbox"/> |
| QUICK CONNECT | | | | |
| Quick coupling | 26 | 2.115-000.0 | For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread. | <input type="checkbox"/> |
| Male coupling | 27 | 2.115-001.0 | Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 x 1.5 external thread. | <input type="checkbox"/> |
| DRUM AND TANK CLEANING | | | | |
| Add-on kit mud sucker | 28 | 2.641-798.0 | For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps. | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR HD 13/18-4 S CLASSIC

1.367-403.0




| | Order no. | Description | |
|--|----------------|--|--------------------------|
| OTHER HP ACCESSORIES | | | |
| Coin remote control | 29 2.644-029.0 | Coin remote control with electronic coin acceptor for connecting a high-pressure cleaner as a pre-wash device. Please have the power outlet and cable provided on site. | <input type="checkbox"/> |
| Jet gun | 30 2.869-067.0 | Short set-up time, easy transport, instant switch off - the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume. | <input type="checkbox"/> |
| NOZZLE UNION / SPACER | | | |
| Nozzle union | | | |
| Nozzle screws | 31 4.112-011.0 | Nozzle screws with protectors for high-pressure and power nozzles | <input type="checkbox"/> |
| HIGH-PRESSURE HOSES | | | |
| Standard with unions on both sides | | | |
| High-pressure hose, 10 m, ID 10, 220 bar, 2 × EASY!Lock | 32 6.110-041.0 | Impressive values and basic equipment: 10 m long high-pressure hose (DN 10) developed for pressures up to 220 bar. | <input type="checkbox"/> |
| High-pressure hose, 20 m, ID 8, 315 bar, 2 × EASY!Lock | 33 6.110-032.0 | 20 m long high-pressure hose (DN 8) equipped with the time-saving and robust EASY!Lock manual screw fitting on both sides. Approved for pressures up to 315 bar. | <input type="checkbox"/> |
| High-pressure hose, 15 m, ID 10, 220 bar, 2 × EASY!Lock | 34 6.110-042.0 | Equipped with innovative EASY!Lock manual screw fitting and suitable for pressures up to 220 bar: 15 m long high-pressure hose (DN 10). | <input type="checkbox"/> |
| High-pressure hose, 20 m, ID 10, 220 bar, 2 × EASY!Lock | 35 6.110-043.0 | 20 m in length and the extremely time-saving and comfortable EASY!Lock manual screw fitting on both sides are some of the main features of this high-pressure hose (DN 10). | <input type="checkbox"/> |
| High-pressure hose, 25 m, ID 10, 220 bar, 2 × EASY!Lock | 36 6.110-044.0 | Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar. | <input type="checkbox"/> |
| High-pressure hose, 40 m, ID 10, 220 bar, 2 × EASY!Lock | 37 6.110-045.0 | 40 m long high-pressure hose with EASY!Lock system for the time-saving manual screw connection (both sides). Nominal size (DN) 10, working pressure up to 220 bar. | <input type="checkbox"/> |
| High-pressure hose, 15 m, ID 12, 210 bar, 2 × EASY!Lock | 38 6.110-059.0 | Designed for working pressures up to 250 bar: High-pressure hose (DN 12) with a length of 15 m. Has the comfortable EASY!Lock manual screw fitting on both sides. | <input type="checkbox"/> |
| High-pressure hose, 40 m, ID 12, 210 bar, 2 × EASY!Lock | 39 6.110-060.0 | With EASY!Lock manual screw fitting and lots of room for manoeuvre thanks to 40 m in length: High-pressure hose (DN 12) with EASY!Lock manual screw fitting on both sides. Suitable for working pressures up to 250 bar. | <input type="checkbox"/> |
| Longlife 400 with unions on both sides | | | |
| High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, 2 × EASY!Lock | 40 6.110-024.0 | 1,5 m short high-pressure hose (DN 8). Comfortable EASY!Lock manual screw fitting on both sides for robust and quick connections. Durable and designed for up to 400 bar pressure. | <input type="checkbox"/> |
| High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, 1 × EASY!Lock / 1 × M22 × 1,5 | 41 6.110-069.0 | 1,5 m long high-pressure hose (DN 8) suitable for up to 400 bar pressure with double steel core. Connections: M 22 × 1,5, as well as the comfortable and quick EASY!Lock manual screw fitting. | <input type="checkbox"/> |
| High-pressure hose Longlife, 10 m, ID 8, 400 bar, 2 × EASY!Lock | 42 6.110-038.0 | Durable, 10 m long high-pressure hose (DN 8) with double steel core and EASY!Lock manual screw fitting on both sides and ANTI!Twist. Approved for 400 bar pressure. | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR HD 13/18-4 S CLASSIC

1.367-403.0



| | | Order no. | Description | |
|--|----|-------------|---|--------------------------|
| HIGH-PRESSURE HOSES | | | | |
| Food industry version with unions on both sides | | | | |
| High-pressure hose food grade, 10 m, ID 8, 250 bar, 2 × EASY!Lock | 43 | 6.110-051.0 | High-pressure hose (ID 6), 10 m long, with grey, non-marking outer covering. Approved for use in the food industry. With quick and robust EASY!Lock hand screw connection at both ends. | <input type="checkbox"/> |
| High-pressure hose food grade, 20 m, ID 8, 250 bar, 2 × EASY!Lock | 44 | 6.110-052.0 | Suitable for use in food industry: 20 m long high-pressure hose (ID 8) with grey, non-marking outer covering, ANTI!Twist and EASY!Lock hand screw connections. | <input type="checkbox"/> |
| Longlife food design with screw connections at both ends | | | | |
| High-pressure hose food grade Longlife, 10 m, ID 8, 400 bar, 2 × EASY!Lock | 45 | 6.110-053.0 | With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends. | <input type="checkbox"/> |
| High-pressure hose food grade Longlife, 20 m, ID 8, 400 bar, 2 × EASY!Lock | 46 | 6.110-054.0 | Durable high-pressure hose with double steel reinforcement and blue, non-marking and animal fat resistant outer covering. 20 m long with EASY!Lock hand screw connections. | <input type="checkbox"/> |
| Special hoses | | | | |
| High-pressure hose curved, 1.5 m, ID 8, 400 bar, 1 × EASY!Lock / 1 × M22 × 1.5 | 47 | 6.110-068.0 | For connection to hose reels: high-pressure hose, with M 22 × 1.5 connection and curved EASY!Lock hand screw connection. 1.5 m long, suitable for up to 400 bar working pressure. | <input type="checkbox"/> |
| PIPE CLEANING | | | | |
| Pipe cleaning hose, ID 6 | | | | |
| Pipe cleaning hose, ID 6, 10 m, max. 250 bar | 48 | 6.110-046.0 | The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). | <input type="checkbox"/> |
| Pipe cleaning hose, ID 6, 20 m, max. 250 bar | 49 | 6.110-008.0 | The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). | <input type="checkbox"/> |
| Pipe cleaning hose, ID 6, 30 m, max. 250 bar | 50 | 6.110-047.0 | The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). | <input type="checkbox"/> |
| Pipe cleaning nozzle | | | | |
| Pipe cleaning dirt blaster D21/060 | 51 | 4.765-002.0 | The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling. | <input type="checkbox"/> |
| Pipe cleaning dirt blaster D21/090 | 52 | 4.765-003.0 | | <input type="checkbox"/> |
| Pipe cleaning dirt blaster D30/060 | 53 | 4.765-005.0 | | <input type="checkbox"/> |
| Pipe cleaning dirt blaster D30/090 | 54 | 4.765-010.0 | | <input type="checkbox"/> |
| Pipe cleaning nozzle 100 | 55 | 5.763-088.0 | Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle. | <input type="checkbox"/> |
| Pipe cleaning nozzle | 56 | 5.763-019.0 | 16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes. | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR HD 13/18-4 S CLASSIC

1.367-403.0



| | Order no. | Description | | |
|---|-----------|-------------|---|--------------------------|
| PIPE CLEANING | | | | |
| Pipe cleaning nozzle | | | | |
| Pipe cleaning nozzle | 57 | 5.763-016.0 | 16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes. | <input type="checkbox"/> |
| | 58 | 5.763-021.0 | 30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes. | <input type="checkbox"/> |
| Rotating pipe cleaning nozzle | 59 | 6.415-440.0 | Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes. | <input type="checkbox"/> |
| FLOOR AND HARD SURFACE CLEANER | | | | |
| Hard Surface Cleaner FRV 30 | | | | |
| FRV 30 Surface Cleaner | 60 | 2.111-010.0 | With the integrated, automatic suction of the dirty water, the FRV 30 makes surface cleaning even more efficient and can be used in both inside and outside areas. There is no longer a need to rinse the surface after cleaning, since the dirty water can be discharged through the 5 m suction hose supplied. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 1000 l/h / 60°C. | <input type="checkbox"/> |
| Rubber lip for FRV 30 | 61 | 2.642-910.0 | For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes. | <input type="checkbox"/> |
| Extension hose 5 m | 62 | 4.440-939.0 | 5m extension hose for FRV 30. Connection sleeve included. | <input type="checkbox"/> |
| Hose fastening attachment kit | 63 | 2.642-528.0 | Suction cup for fixing the suction hose to smooth surfaces. | <input type="checkbox"/> |
| Dirt trap attachment kit | 64 | 2.642-532.0 | Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas. | <input type="checkbox"/> |
| FR 30 Me surface cleaner | | | | |
| Hard Surface Cleaner FR 30 Me | 65 | 2.111-013.0 | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. | <input type="checkbox"/> |
| Hard Surface Cleaner FR 50 | | | | |
| Surface Cleaner FR 50 Me | 66 | 2.111-023.0 | Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. | <input type="checkbox"/> |
| Machine-specific nozzle kits for FR | | | | |
| Nozzle kit for FR, 1100 l/h - 1300 l/h | 67 | 2.639-188.0 | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (1100 to 1300 l/h). | <input type="checkbox"/> |
| Machine-specific nozzle kits for FRV | | | | |
| Nozzle kit for FRV, 080 | 68 | 2.642-982.0 | Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30. | <input type="checkbox"/> |
| FRV 30 Me surface cleaner | | | | |
| FRV 30 Me Surface Cleaner | 69 | 2.111-012.0 | Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. | <input type="checkbox"/> |
| Extension hose FRV 30 Me and FRV 50 Me | 70 | 4.441-040.0 | 5 m extension hose for FRV 30 Me. Includes connecting adapter. | <input type="checkbox"/> |

Available accessories.

ACCESSORIES FOR HD 13/18-4 S CLASSIC

1.367-403.0



| | | Order no. | Description | |
|---|----|-------------|---|--------------------------|
| FLOOR AND HARD SURFACE CLEANER | | | | |
| Surface Cleaner FR 50 Me | | | | |
| FRV 50 Me surface cleaner | 71 | 2.111-024.0 | Surface cleaning with automatic suction of the dirty water for very large surfaces - this means the FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C. | <input type="checkbox"/> |
| FOAM SYSTEMS | | | | |
| Cup foam lance | | | | |
| Cup foam lance Advanced 3, 900 l/h - 2500 l/h | 72 | 4.112-065.0 | Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Eco brass for high-pressure cleaners from Kärcher. | <input type="checkbox"/> |
| Cup foam lance DUO Advanced 3, 900 l/h - 2500 l/h | 73 | 4.112-069.0 | DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank. | <input type="checkbox"/> |
| Cup foam lance Basic 3, 900 l/h - 2500 l/h | 74 | 4.112-055.0 | High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality. | <input type="checkbox"/> |
| 1-litre cleaning agent container for cup foam lance basic | 75 | 5.071-414.0 | For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). | <input type="checkbox"/> |
| 1-litre cleaning agent container for cup foam lance advanced | 76 | 6.414-050.0 | Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0). | <input type="checkbox"/> |
| Inno Foam Kit | | | | |
| Inno Foam Set with detergent injector | 77 | 2.112-000.0 | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection. | <input type="checkbox"/> |
| Easy Foam Set | | | | |
| Easy Foam Set with RM injector | 78 | 2.112-010.0 | HP foam system for use with HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately. | <input type="checkbox"/> |
| Nozzle kits for Inno/Easy Foam Set | | | | |
| Nozzle kit 110 for Inno / Easy Set for HD 13/18 | 79 | 2.111-022.0 | Optimal adaptation to different machine outputs for economic use. | <input type="checkbox"/> |
| Foam nozzle mounting kit | | | | |
| Foam nozzle attachment kit | 80 | 2.112-013.0 | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary. | <input type="checkbox"/> |
| MIXERS AND INJECTORS | | | | |
| Cleaning agent injector | | | | |
| Cleaning agent injector for high and low pressure (without nozzles) | 81 | 4.637-032.0 | Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%. | <input type="checkbox"/> |
| Cleaning agent injector for high pressure (without nozzle) | 82 | 4.637-033.0 | Cleaning agent dosage at high pressure 3 - 5 % | <input type="checkbox"/> |
| Stainless steel injector kit for HDS 12/18-4S | 83 | 6.645-763.0 | The stainless steel injector is supplied as a kit with a suction hose and vacuum filter for the HDS 12/18-4 S High-pressure cleaner - fits on the high-pressure outlet of the machine. | <input type="checkbox"/> |
| Nozzle insert with order no. 4.637-032.0 | | | | |
| Nozzle insert from 1,100 l/h - HD | 84 | 4.769-002.0 | For high pressure with machines above 1.100 l/h | <input type="checkbox"/> |

Available accessories.

ACCESSORIES FOR HD 13/18-4 S CLASSIC

1.367-403.0



| | Order no. | Description | |
|---|-----------|-------------|--|
| MIXERS AND INJECTORS | | | |
| Nozzle insert with order no. 4.637-032.0 | | | |
| Nozzle insert from 1,100 l/h - ND | 85 | 4.769-006.0 | For low pressure with machines above 1.100 l/h <input type="checkbox"/> |
| COUPLING PARTS | | | |
| Rotary coupling | | | |
| Rotary coupling | 86 | 4.111-021.0 | Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection <input type="checkbox"/> |
| Connector | | | |
| Screw socket for surface cleaners and Servo Control controllers | 87 | 4.111-022.0 | For attaching high-pressure nozzles and accessory parts to the HD trigger gun (with nozzle screws) - 1 × M 22 × 1.5/1 × M 18 × 1.5. <input type="checkbox"/> |
| Y distributor | 88 | 4.111-024.0 | Offers the option to connect two spray units to the machine. Installation on the high pressure outlet. <input type="checkbox"/> |
| Short spray unit | 89 | 4.111-038.0 | For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles. <input type="checkbox"/> |
| EASY!Lock adapter | | | |
| Adapter 1 M22AG-TR22AG | 90 | 4.111-029.0 | Adapter 1 to connect the old hose with the new hose <input type="checkbox"/> |
| Adapter 2 M22IG-TR22AG | 91 | 4.111-030.0 | Adapter 2 to connect the old device with the new hose and the old gun with the new hose <input type="checkbox"/> |
| Adapter 3 M22IG-TR22AG | 92 | 4.111-031.0 | Adapter 3 to connect the old gun with the new spray lance and new servo regulator <input type="checkbox"/> |
| Adapter 4 TR22IG-D11 | 93 | 4.111-032.0 | Adapter 4 to connect the new gun with the old swivel hose <input type="checkbox"/> |
| Adapter 5 TR22IG-M22AG | 94 | 4.111-033.0 | Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance <input type="checkbox"/> |
| Adapter 6 TR22IG-M22AG | 95 | 4.111-034.0 | Adapter 6 to connect the new device with the old hose and the old hose with the new gun <input type="checkbox"/> |
| Adapter 7 M18IG-TR20AG | 96 | 4.111-035.0 | Adapter 7 to connect the old spray lance with the new nozzle <input type="checkbox"/> |
| Adapter 8 TR20IG-M18AG | 97 | 4.111-036.0 | Adapter 8 to connect the new spray lance with the old nozzle <input type="checkbox"/> |
| Adapter hose extension 9 TR | 98 | 4.111-037.0 | Adapter 9 to connect the new hose with the new hose <input type="checkbox"/> |

Available accessories.

ACCESSORIES FOR HD 13/18-4 S CLASSIC

1.367-403.0



| | Order no. | Description | |
|--|-----------|-------------|---|
| COUPLING PARTS | | | |
| EASY!Lock adapter | | | |
| Adapter 12 rotary coupling EASY!Lock 22 IG - M22 x 1.8 AG | 99 | 4.111-046.0 | Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection |
| HOSE REELS | | | |
| Automatic, self-winding hose reels for wall mounting | | | |
| Automatic plastic hose reel incl. high-pressure hose, 15 m | 100 | 2.639-257.0 | Spring-mounted and ready-to-use automatic hose reel for wall mounting. Simplifies handling of the high-pressure hose, shortens set-up times and increases occupational safety. |
| Automatic hose reel, powder-coated steel / plastic, 20 m | 101 | 6.392-074.0 | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic. |
| Automatic stainless steel / synthetic material hose drum, 20 m | 102 | 6.392-083.0 | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic. |
| Automatic hose reel, coated, 20 m | 103 | 6.392-106.0 | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose. |
| Hose reel, automatic, basalt grey-coated, 20 m | 104 | 6.392-105.0 | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife). |
| Automatic hose reel, stainless steel, includes swivel holder, 20 m | 105 | 6.392-076.0 | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose. |
| Automatic stainless steel hose reel, 40 m | 106 | 6.392-442.0 | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit). |
| Zinc-coated swivel holder | 107 | 2.639-931.0 | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel. |
| Stainless steel swivel holder | 108 | 2.641-867.0 | Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose. |
| Manual hose reel attachment kit | | | |
| High-pressure hose reel attachment kit for the Classic super class | 109 | 2.639-336.0 | For retrofitting high-pressure cleaners from the Classic super class: attachment kit with high-pressure hose reel, high-pressure hose (20 m), connection hose, brackets and necessary small parts. |
| FACADE AND SOLAR PANEL CLEANING | | | |
| Brushes | | | |
| Brush hard | 110 | 6.960-133.0 | Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher. |
| Brush medium | 111 | 6.960-134.0 | Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher. |
| Brush soft | 112 | 6.960-135.0 | For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems. |

Available accessories.

ACCESSORIES FOR HD 13/18-4 S CLASSIC

1.367-403.0



| | | Order no. | Description | |
|--|-----|-------------|--|--------------------------|
| FACADE AND SOLAR PANEL CLEANING | | | | |
| Brushes | | | | |
| iSolar 800 Advanced (1100-1300 l/h) | 113 | 6.368-095.0 | For water flow rates of 1,100-1,300 l/h: The 800-mm iSolar water-driven brush head with two contra-rotating disc brushes and flexible angle joint ensures that photovoltaic systems are given an even clean. | <input type="checkbox"/> |
| iSolar 400 Advanced | 114 | 6.368-093.0 | The iSolar 400 water-driven disc brush (working width 400 mm) is designed for water flow rates of 1,100-1,300 l/h. For small to medium-sized photovoltaic systems (including elevated systems). | <input type="checkbox"/> |
| Telescopic lances | | | | |
| TL low pressure adapter | 115 | 4.580-097.0 | TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes. | <input type="checkbox"/> |
| Telescopic lance TL 7 F | 116 | 4.762-609.0 | Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension. | <input type="checkbox"/> |
| Telescopic lance TL 7 H | 117 | 4.762-610.0 | Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix. Telescopic thanks to quick-release fastenings. Up to 7 m reach. | <input type="checkbox"/> |
| Telescopic lance TL 10 H | 118 | 4.762-611.0 | Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners. | <input type="checkbox"/> |
| Telescopic lance TL 10 C | 119 | 4.762-612.0 | Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels. | <input type="checkbox"/> |
| Telescopic lance TL 14 C | 120 | 4.762-613.0 | Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners. | <input type="checkbox"/> |
| TL high pressure adapter | 121 | 4.775-154.0 | TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals. | <input type="checkbox"/> |
| Water softening | | | | |
| WS 50 | 122 | 6.368-463.0 | The mobile WS 50 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water. | <input type="checkbox"/> |
| WS 100 | 123 | 6.368-464.0 | The mobile WS 100 water softening unit prevents lime residue from forming on cleaned surfaces. This is achieved by an ion-exchange resin that removes the dissolved limescale from the water. | <input type="checkbox"/> |
| WS Regenerator | 124 | 6.368-465.0 | With the WS Regenerator regeneration system, the softening cartridges of the water softening units WS 50 and WS 100 can be backflushed and regenerated at the push of a button. | <input type="checkbox"/> |
| Hoses | | | | |
| iSolar HP hose 7 | 125 | 6.392-978.0 | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod. | <input type="checkbox"/> |
| iSolar HP hose 10 | 126 | 6.392-977.0 | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod. | <input type="checkbox"/> |

Available accessories.

ACCESSORIES FOR HD 13/18-4 S CLASSIC

1.367-403.0



| | Order no. | Description | |
|---|-----------|-------------|---|
| FACADE AND SOLAR PANEL CLEANING | | | |
| Hoses | | | |
| iSolar HP hose 14 | 127 | 6.392-976.0 | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod. <input type="checkbox"/> |
| Attachment kits and adapters | | | |
| iSolar fall protection | 128 | 6.988-152.0 | Certified personal security system for rooftop work. Contents: Travelling fall arrestor with shock absorber and 15 m kernmantle rope, harness, anchoring sling and sheet steel case. <input type="checkbox"/> |
| WET BLASTING ATTACHMENT | | | |
| Nozzle kits for wet jet unit | | | |
| Nozzle kit for 080 wet jet unit | 129 | 2.112-029.0 | Consisting of wet jet nozzle and nozzle insert - only for use in combination with wet jet unit 4.115-000.0 4.115-006.0. <input type="checkbox"/> |
| Boron carbide nozzle | | | |
| Boron carbide, for machines from 1,000 l/h | 130 | 6.415-083.0 | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation. <input type="checkbox"/> |
| DRUM AND TANK CLEANING | | | |
| Barrel and tank cleaning | | | |
| Barrel cleaner BC 14/12 | 131 | 2.112-020.0 | The BC 14/12 barrel cleaner is a spray unit for the interior cleaning of containers and barrels - especially oak barrels with a capacity of between 225 and 600 litres. <input type="checkbox"/> |
| Spray head HKF 30/14-E | 132 | 6.751-061.0 | Compact interior cleaning head made of stainless steel for cleaning the interiors of drums and containers with openings of 65 mm or more. Offers an impressively low weight and constant rotation speed by means of an electric motor. <input type="checkbox"/> |
| Nozzle kit for spray head HKF 50 (3.631-009.0 / 3.631-039.0) | | | |
| Nozzle 045 for 2-nozzle operation HKF 50 | 133 | 6.415-446.0 | Nozzle for dual-nozzle operation <input type="checkbox"/> |
| High-pressure full jet nozzle 090 for interior cleaning heads | 134 | 6.415-447.0 | High-pressure full jet nozzle 090 for interior cleaning heads with a spray angle of 0°, made of hardened stainless steel and with 1/8-inch thread. <input type="checkbox"/> |
| Double grip for precise control of spray head | 135 | 2.863-036.0 | Double handle. Precise control of the spray head <input type="checkbox"/> |
| 1/8" screw plug for interior cleaning heads | 136 | 5.411-061.0 | Screw plug for high-pressure interior cleaning heads with 1/8-inch thread. <input type="checkbox"/> |
| WATER CONNECTION | | | |
| Geka coupling | | | |
| Geka connector with hose barb, R 1" | 137 | 6.388-465.0 | with hose barb <input type="checkbox"/> |
| Geka connector with internal thread, R 1" | 138 | 6.388-458.0 | with female thread <input type="checkbox"/> |
| Suction filter | | | |
| Water suction filter | 139 | 6.414-956.0 | Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve <input type="checkbox"/> |
| Suction filter with check valve | 140 | 4.730-012.0 | Brass suction filter suitable for ponds, storage tanks, etc. With check valve. <input type="checkbox"/> |

Available accessories.

ACCESSORIES FOR HD 13/18-4 S CLASSIC

1.367-403.0



142



143



144-145



146



147



148

| | | Order no. | Description | |
|--|-----|-------------|--|--------------------------|
| WATER CONNECTION | | | | |
| Water fine filter | | | | |
| Universal water fine filter, 25 µm | 141 | 2.637-020.0 | Water fine filter, mesh size 25 µm, max. temperature 50 °C. Protects the machine from small dirt particles in the water. Water volume up to 1200 l/h. 3/4" connection, with 1" adapter. | <input type="checkbox"/> |
| Water fine filter, with adapter | 142 | 4.730-102.0 | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1". | <input type="checkbox"/> |
| Water fine filter, 100 µm, R 1" | 143 | 2.638-270.0 | Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1". | <input type="checkbox"/> |
| Water supply hose | | | | |
| Water supply hose | 144 | 4.440-207.0 | NW 19 R1" / R 3/4", up to 85 °C, for pick-up | <input type="checkbox"/> |
| | 145 | 4.440-270.0 | NW 19 R1" / R1", up to 85 °C | <input type="checkbox"/> |
| WASHING BRUSHES | | | | |
| Push-on washing brush | | | | |
| Push-on wash brush | 146 | 4.113-001.0 | For universal use for surface cleaning. Mounted using clamp directly at the spray lance. TR thread connection | <input type="checkbox"/> |
| Rotating washing brush | | | | |
| Rotating wash brush for > 1000 l/h machines, nylon bristles | 147 | 4.113-002.0 | Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 × 1.5 (replaceable brush insert). | <input type="checkbox"/> |
| Rotating wash brush for > 800 l/h machines, natural bristles | 148 | 4.113-005.0 | | <input type="checkbox"/> |

Available accessories.