


OSCILLATING SPRINKLER OS 5.320 S

Oscillating sprinkler OS 5.320 S for watering medium-sized and large areas and gardens. Adjustable flow control (0-max.). Covers up to 320 m².



Order no.

2.645-134.0

Technical data

EAN code		4039784426344
Sprinkling area (2 bar)		60 - 190 m ² (2 bar)
Sprinkling area (4 bar)		100 - 320 m ² (4 bar)
Width of spray (2 bar)	m	12
Width of spray (4 bar)	m	16
Area coverage (2 bar)	m	5 - 16
Area coverage (4 bar)	m	6 - 20
Colour		Black
Weight	kg	0.8
Weight incl. packaging	kg	0.9
Dimensions (L × W × H)	mm	546 × 160 × 88



Continuous reach adjustment

- Precise watering.

Loop for hanging the device integrated into the handle

- For simple storage/hanging.


Adjustable width of spray

- Different spray angles for targeted watering.

COMPATIBLE MACHINES

- Wassertimer WT 5

ACCESSORIES FOR OSCILLATING SPRINKLER OS 5.320 S 2.645-134.0



		Order no.	Description	
HOSES				
PrimoFlex Plus hose 1/2" - 20 m	1	2.645-144.0	20 m PrimoFlex® Plus quality garden hose (1/2"). With pressure-resistant reinforcement mesh. Contains no substances that are harmful to health. Bursting pressure: 45 bar. High temperature resistance from -20 to 65 °C.	<input type="checkbox"/>
HOSE CONNECTION SYSTEMS				
Universal hose coupling Plus	2	2.645-193.0	Universal hose coupling plus with soft plastic recessed grips for comfortable handling. Compatible with all click systems.	<input type="checkbox"/>
Universal hose coupling Plus with Aqua Stop	3	2.645-194.0	Universal hose coupling plus with Aqua Stop and soft plastic recessed grips for comfortable handling. Compatible with all click systems.	<input type="checkbox"/>
G3/4 tap adaptor with G1/2 reducer	4	2.645-006.0	Extremely tough tap connector 3/4" thread with 1/2" thread reducer. The reducer allows connection to two thread sizes. Compatible with all click systems.	<input type="checkbox"/>

■ Included in the scope of supply. Available accessories. Detergents.